

SAFETY DATA SHEET

Issue Date: March 5, 2014

Page 1 of 7

SECTION 1: IDENTIFICATION

Product Identifier

Product Name: Flash

Recommended Use of the Chemical and Restrictions on Use

Recommended Use: Oven & Grill Cleaner

Details of the Supplier of the Safety Data Sheet

Supplier Address: Luseaux Laboratories, Inc. Luseaux Laboratories Inc.
4625 N Santa Fe Drive or 16816 Gramercy Place
Kingman, AZ 86401 Gardena, CA 90247

Emergency Telephone Number

Company Phone Number: Arizona Location: 928-692-0192
California Location: 310-324-1555

Emergency Telephone: CHEMTREC: 1-800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

Appearance: Light amber clear liquid **Physical State:** Liquid **Odor:** Mild butyl odor

Classification

Skin corrosion/irritation	Category 1C
Serious eye damage/eye irritation	Category 1



Signal Word

Danger

Hazard Statements

Causes severe skin burns and eye damage.

Precautionary Statements – Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling.

Precautionary Statements – Response

Immediately call a poison center or doctor/physician.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.

IF INALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

Precautionary Statements – Storage

Store locked up.

Precautionary Statements – Disposal

Dispose of contents/container to an approved waste disposal plant.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight %
Sodium Hydroxide	1310-73-2	Not identified*
Ethylene Glycol Monobutyl Ether	111-76-2	Not identified*

*The specific percentages are not identified due to "Trade Secret" status. In emergency situation, further information may be obtained by calling the emergency information number listed above. Reference 29 CFR 1910.1200

SECTION 4: FIRST AID MEASURES

First Aid Measures

Eye Contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediately call a poison center or doctor/physician.

Skin Contact: Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid if irritation develops or persists. Wash clothing before reuse.

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.

Ingestion: If swallowed, rinse mouth. Do NOT induce vomiting. Drink large quantities of water without delay. Drink milk or milk of magnesia. Never give anything by mouth to a person who is unconscious or convulsing.

Most Important Symptoms and Effects, both Acute and Delayed

Symptoms Causes severe skin burns and eye damage. Eye contact may result in redness, pain, blurred vision, burning sensation. Corrosive to mucous membranes. Ingestion may lead to stomach or esophageal burns, perforations or strictures.

Indication of any Immediate Medical Attention and Special Treatment Needed

Note to Physicians Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water. Carbon dioxide (CO₂). Dry chemical.

Unsuitable Extinguishing Media: Not determined.

Specific Hazards Arising from the Chemical

Material is corrosive. Product is not flammable.

Hazardous Combustion Products: Caustic solutions will liberate flammable hydrogen gas from active metals. Extreme temperatures may liberate unidentified, possibly harmful organics and other compounds.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSNA/NIOSH (approved or equivalent) and full protective gear. Floor will become slippery if material is released and mixed with water.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions: Use personal protective equipment as required. Spills may be slippery.

Environmental Precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater.

Methods and Material for Containment and Cleaning Up

Methods for Containment: Prevent further leakage or spillage if safe to do so. For large spills, dike well ahead to liquid. Recover product for reuse when possible. For small spills, absorb on polypads or other suitable non-reactive absorbent materials. Collect in suitable containers for disposal.

Methods for Cleaning Up: Place collected waste in DOT approved containers for disposal.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Advice on Safe Handling: Handle in accordance with good industrial hygiene and safety practice. Use personal protection recommended in Section 8. Avoid contact with skin, eyes or clothing. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands, and any exposed skin thoroughly after handling.

Conditions for Safe Storage, Including and Incompatibilities

Storage Conditions: Keep container tightly closed and store in a cool, dry and well-ventilated place. Store locked up. Store away from food stuffs. Protect from extreme temperatures.

Incompatible Materials: Strong acids. Aluminum. Magnesium.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Sodium hydroxide 1310-73-2	Ceiling: 2 mg/m ³	TWA: 2 mg/m ³ (vacated) Ceiling: 2 mg/m ³	IDLH: 10 mg/m ³ Ceiling: 2 mg/m ³
Ethylene Glycol Monobutyl Ether, 111- 76-2	TWA: 20 ppm S	TWA: 50 ppm S	-
Trade Secret*	STEL: 6 ppm	TWA8: 6 ppm	-

Appropriate Engineering Controls

Engineering Controls Apply technical measures to comply with occupational exposure limits. Eye wash stations. Showers.

Individual Protections Measures, such as Personal Protective Equipment

Eye/Face Protection: Chemical anti-splash safety goggles.

Skin and Body Protection: Rubber gloves or vinyl gloves. Rubber apron. Rubber boots. Long sleeve shirt and long pants.

Respiratory Protection: Ensure adequate ventilation, especially in confined areas. In case of inadequate ventilation, wear respiratory protection.

General Hygiene Considerations: Wash contaminated clothing before reuse. Wash face, hands and any exposed skin thoroughly after handling.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information and Basic Physical and Chemical Properties

Physical State: Liquid

Odor: Mild butyl odor

Appearance: Amber clear liquid

Color: Amber

Odor Threshold: Not determined

Property	Value	Property	Value
pH – 1% solution	> 12.0	Melting/freezing point	Not determined
Boiling point	232°F	Flash point	Not flammable
Evaporation rate	Not determined	Flammability	Not flammable
Flammability limits/ air	Not determined	Vapor pressure	12 mm Hg @ 68 Deg F
Vapor density	Unknown	Specific gravity	1.11
Water solubility	Soluble in all proportions	Solubility in other solvents	Not determined
Partition coefficient	Not determined	Auto-ignition temp	Not determined
Decomposition temp	Not determined	Kinematic viscosity	Not determined
Dynamic Viscosity	Not determined	Explosive properties	Not determined
Oxidizing properties	Not determined	Bulk Density	Not applicable

SECTION 10: STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Keep out of reach of children. Extreme temperatures.

Incompatible Materials

Strong acids. Aluminum. Magnesium.

Hazardous Decomposition Products

Caustic solutions will liberate flammable hydrogen gas from active metals. Extreme temperatures may liberate unidentified, possibly harmful organics and other compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure**Product Information**

Eye Contact	Causes severe eye damage.
Skin Contact	Causes severe skin burns.
Inhalation	Avoid breathing vapors or mists.
Ingestion	Do not taste or swallow.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Sodium hydroxide 1310-73-2	-	= 1350 mg/kg (Rabbit)	-
Ethylene Glycol Monobutyl Ether, 111- 76-2	= 470 mg/kg (Rat)	= 2270 mg/kg (Rat) = 220 mg/kg (Rabbit)	= 2.21 mg/L (Rat) 4h = 450 ppm (Rat) 4h
Trade Secret*	= 1.07 ml/kg (Rat)	= 2.46 ml/kg (Rabbit)	-

Information on Physical, Chemical and Toxicological Effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Carcinogenicity Not classifiable as a human carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethylene Glycol Monobutyl Ether, 111- 76-2	A3	Group 3		

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)
A3 – Animal Carcinogen
IARC (International Agency for Research on Cancer)
Group 3 IARC components are “not classifiable as human carcinogens”

Numerical Measures of Toxicity-Product

Not determined

SECTION 12: ECOLOGICAL INFORMATION

Not determined

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Sodium Hydroxide, 1310-73-2	Toxic; Corrosive

SECTION 14: TRANSPORT INFORMATION

Based on package size, product may be eligible for limited quantity exception. Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT NA 1760, COMPOUND, CLEANING, LIQUID (Contains Sodium Hydroxide) 8, PG III,

SECTION 15: REGULATORY INFORMATION

International Inventories**Legend:**

Not determined

US Federal Regulations**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Sodium Hydroxide, 1310-73-2	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

SARA 313

Chemical Name	CAS No	Weight %	SARA 313 – Threshold Values %
Ethylene Glycol Monobutyl Ether	111-76-2	1-10	1.0

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Component	CWA – Reportable Quantities	CWA – Toxic Pollutants	CWA – Priority Pollutants	CWA – Hazardous Substances
Sodium Hydroxide, 1310-73-2	1000 lb			X

US State Regulations**California Proposition 65**

Calif. Prop. 65 Warning: This product may contain a trace amount of one or more of the chemicals on the California list of known carcinogens or substances known to cause birth defects or other reproductive harm. These are not added to the product but occur naturally in the raw materials or processing equipment.

SECTION 16: OTHER INFORMATION

<u>NFPA</u>	Health Hazards	Flammability	Reactivity	Personal Protection
	3	0	0	F

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of publication. The information is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet